



# Circulating Fans

## Poultry House Ceiling Fans



### Features:

- Engineered and designed for spacious applications where maximum floor coverage is required.
- Reversible motor for both winter heat destratification and summer time cooling.
- All fans are sealed and suitable for high moisture applications.
- Short 8" downrod for low ceilings.

### Performance Data & Specifications:


- Fan Size: ..... 56"
- Max RPM: ..... 319
- Air Velocity @ Max RPM: ..... 660
- Amps high: ..... 0.83
- Watts High: ..... 100
- Download Length: ..... 8"
- Shipping Wgt.: ..... 24lbs.

## Plastic Box Circulating Fans



### Features:

- 36" and 48" models.
- Patented design provides higher air volumes at maximum efficiency (U.S. patent #5,803,709).
- The poly box design is virtually self-cleaning and will not rust, peel, chip or rot.
- Fans are provided with 2' x 2' galvanized wire mesh screens.
- Motors are high efficiency, single or three phase.
- The fans can be suspended from the corner clips provided on the fans or easily angled the hanging bracket kit accessories.



### Mounting Options:

- Hanging Bracket Kit.

(36" with hanging bracket.)

### Performance Data & Specifications

Size	H.P.	Blade Paddle	Volts	Amps	Phs	RPM	Speed	CFM O" SP	CFM / Watt	Dimensions
36"	1/2	3	115/230	6 / 3	1	850	Single	12,200	21.3	40" x 40" x 13"
36"	1/2	3	208-230/460	2.4/1.2	3	850	Single	12,200	23.0	40" x 40" x 13"
48"	1	3	230	5	1	850	Single	21,000	22.4	52" x 52" x 11"
48"	1	3	208-230/460	5.2/2.6	3	850	Single	21,000	24.0	52" x 52" x 11"

## Metal Box Circulating Fans



### Features:

- 48" Belt Drive Models
- High efficiency single and three phase motors
- Strong, galvanized steel construction
- 2 x 2 galvanized wire mesh screens
- High quality rotary belt tensioner
- Easily accessible rubber belt

### Product Specifications

Size	Motor Specifications				Performance at 0.00 Static Pressure					Dimensions
	HP	Volts	Phs	Hz	Amps	Volts	Rpm	CFM	CFM/w	
48"	1	115/230	1	60	4.83	230	590	20,600	19.0	54.5" x 54.5" x 24"
48"	1	208-230/460	3	60	1.92	460	585	20,300	18.4	
48"	1	220-240/380-415	3	50	1.74	380	545	19,590	23.4	



**Big Dutchman.**

#### Germany

P.O. Box 11 63 • D-49360 Vechta • Germany  
tel +49 (0) 44 47 801 0 • fax +49 (0) 44 47 801 237  
www.bigdutchman.com • big@bigdutchman.de

#### Asia-Pacific

No. 25 Jalan Pemberita (U1/49), Temasya Industrial Park  
40150 Shah Alam • Selangor Darul Ehsan • Malaysia  
tel +603 5569 2320 • fax +603 5569 5930  
bdasia@bda.com.my

#### USA

P.O. Box 1017 • Holland, MI 49422-1017 • USA  
tel +1 616 392 5981 • fax +1 616 392 6188  
www.bigdutchman.com • bigd@bigdutchmanusa.com

#### Brazil

Caixa Postal 84 • Rua Victorio Milani, 125  
Caxias do Sul, RS 95095-107 • Brasil  
tel +55 (0) 54 226 2200 • fax +55 (0) 54 226 1424  
www.bigdutchman.com.br • bigdutchmanbrasil@bigdutchman.com.br

In the interest of progress,  
technical details are subject  
to change.